



AMPAG BOXER YM TRANSIT

STRAPPING MACHINE

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

Fully automatic strapping with PP strap

The Ampag Boxer YM TR strapping machine is a very fast strapping machine with strapping head on the side of the machine in the stainless steel version it is suitable for use in a humid working environment. Due to the strapping head on the side the strapping machine is resistant to dust, sand and dirt. The Ampag Boxer YM TR is suitable for strapping with 5, 9 and 12 mm PP strap. The machine is low-maintenance and extremely suitable for intensive use with high production numbers.

Advantages

- For PP strap 5 – 9 – 12 mm
- Automatic strap input and output
- Strapping head on the side - resistant to dust, sand and dirt
- Stainless steel version – for humid working environment
- Ready for operation within 30 seconds
- Up to 35 straps per minute
- End of strap signaling
- Strapping with welding tongue
- Extremely suitable for integration into existing lines
- Complete system with transport and control



Technical data:	
Speed	Up to 35 straps/minute
Consumable	PP strap: 5, 9 of 12 mm
Max. package weight	Dependent on transport system
Strap coil	Core 200 mm Outer diameter 420 mm Width: 190 mm
Strap tension	50 – 800 N
Strapping	Heat seal
Noise	78 - 85 dB(A)
Warm up time	30 seconds
Power supply	400 V, 3 phase, 50 Hz
Weight	ca. 230 kg