



## Strapping hand tool CMT 50

For medium-heavy packages in industry



**Plastic strapping handtool**

- ✓ Tension up to 2.300 N
- ✓ The alternative to steel strapping

Wherever medium-heavy packages need high strap tension and where manual strapping is required in several locations, the CMT 50 is the optimal choice. The strap is tensioned manually (with tension plate, separate strap input) up to 2.300 N, the strap is then joined with a friction seal powered from the battery. The tool is supplied with an automatic charger and a long-life industrial.

**Technical data: CMT 50**

Weight:	4.0 kg (incl. battery)
Dimensions:	400 x 130 x 200 mm
Strap tension:	0 – 2.300 N (depending on strap quality and package)
Seal method:	friction weld
Insertion:	separate strap input

**Strapping material**

Type:	Polyester (PET) and Polypropylene (PP)	
Dimensions:	Width	Thickness
PET	9 – 19 mm	0,5 – 1,0 mm
PP	9 – 16 mm	0,5 – 1,0 mm

**Technical data: Battery**

NiCd-Battery:	12 V
Number of cycles per battery charge:	0 – 200 (depending on strap quality)
Number of charges:	Up to 2.000

**Technical data: Charger**

Supply:	230 V
---------	-------

**Accessories**

Strap dispensers PPQ, QPWK, QPWM, QPWP



Subject to changes.

Cyklop UK Limited  
Unit 2, Generation Business Park  
Barford Road  
St. Neots, Cambridgeshire, PE19 6YQ

Phone: +44 (0)1480 216777  
Fax: +44 (0)1480 216779  
homepage: [www.cyklop.co.uk](http://www.cyklop.co.uk)  
e-mail: [info@cyklop.co.uk](mailto:info@cyklop.co.uk)

