

ELASTIC STRING TYING MACHINE MODEL: AXRO MD 35/60



### AXRO-MD 35/60

## For binding, bundling and attachment jobs

The AXRO-MD 35/60 is designed for strapping long shaped products and is able to bundle products with a feed through depth up to 600 mm! The machine is provided with the well-known AXRO-gripping-and-knotting technology. The AXRO-MD 35/60 is suitable for many difgferent industries.


#### Advantages


- Moveable, 4-wheel support frame (option)Easy to built in an automatic processing line
  - Easy to operate
  - All functions are operated automatically by startsensor, footswitch, PLC
  - Robust, durable, very reliable
  - Minimum maintenance
  - Strongly reduced noise





**Operation** Products are passed along the table surface through the pre-draped elastic string. The machine switches on: folds the Elastic string around the product into the tying mechanism". The Elastic string will be knotted and cut off. The arm will return into the start position with the Elastic string ready for a new product. The tied product can be removed from the machine.

Data









	AXRO-MD 35			AXRO-MD 60		
Capacity	3.500 cycles/h			3.500 cycles/h		
Feed through height	150 mm			150 mm		
Depth	350 mm			600 mm		
Machine weight	80 kg			80kg		
Power supply	230V, 110V, 50Hz, 1 ph.		230V, 110V, 50Hz, 1 ph.			
String tension	adjustable			adjustable		
Bench	Stainless Steel		Stainless Steel			
Trigger	foot switch, photocel, laser, PLC		foot switch, photocel, laser, PLC			
Elastic string	Cylastic PES	Cylastic PC 13	300	Cylastic 3K		
Breaking strength	55 N		65 N	110 N		
Stretch	260%	2	45%	310%		

Versions Options

Vertical construction, Stainless steel 4-wheel support frame, photocel

# WWW.CYKLOP.NL

## +31 38 4675800

Cyklop Nederland B.V. Benjamin Franklinstraat 5 8013 NC Zwolle info@cyklop.nl



